

# LUMI-S WH 180 E1/ST XWB

Kod ElektriKo: 106860 Kod Glamox: LUM593376



**UWAGA:** Zdjęcie poglądowe dla całej rodziny produktów.

## Dane techniczne:

- Czas pracy na baterii **1,0 h**
- Czas pracy na baterii **1,0 h**

General: Product shape: Square

Certificates: Certification: CNBOP,HACCP

Technical Data: Minimum TA (°C): 0, Maximum TA (°C): 40, IK classification: 05, IP classification: 65

Light Technical Data: Light source: LED, Lumen Out (lm): 180, Lumen Per Watt (lm/W): 55, Lamp colour temp (K): 5700, Colour Rendering Index: >70, Light Source Included: Yes, PstLM: Flicker (<): 0.08, SVM: Stroboscopic Visibility Measure (<): 0.03

Driver / Ballast: Type of LED Driver: HF: Non dimmable, Number of Driver: 1

Lifetime: LED Lifetime L70B50 Ta25 (h): 100 000, LED Lifetime L80B50 Ta25 (h): 100 000, LED Lifetime L90B50 Ta25 (h): 100 000

Electrical Data: Main Feed AC (V) Min: 220, Main Feed AC (V) Max: 240, Main Feed Frequency Min: 50, Main Feed Frequency Max: 60, Total Consumption (W): 3.30, IEC Protection Class: II

Emergency: Emergency Type: ST = Self test, Duration (hrs): 1, Charging power consumption (Emg) (W): 1.50, Lumen Out In Emergency (lm): 180, Percentage Light Out In Emergency: 100, Battery Type: LiFePO4, Battery Form:

SideBySide, Battery mAh: 1,000, Battery Voltage (V): 6.40, Battery Sparepart No: SP-MY-413-LI1000F, Battery Termination: NS39

Optic: Optic Name: XWB - Extreme wide beam, Diffuser Material: PMMA, Diffuser Material Design: Clear

Housing: Body Material: Polycarbonate, Body Colour: WH - White, Main Body Colour Name: White

Dimensions: Length (mm): 130, Width (mm): 130, Height (mm): 44, Item Net Weight (kg): 0.34

Termination: Termination: 5x2.5mm2 Push In

Cable Inlet: Number of Glands: 1

Mounting: Product Mounting: Ceiling surface

Logistic Data: Item Gross Weight (kg): 0.37

Ceiling mounted escape route emergency lighting according to all relevant European standards.

E1 / ST means that this item has a built-in emergency light for minimum 1 hour duration. It tests itself according to European emergency light standards. Indicator LEDs on the product communicate the test results.

Item No.	LUM593376
GTIN	5901155933760
Stock status	A